



(12) **United States Patent**
Ohga et al.

(10) **Patent No.:** **US 9,636,681 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **HOLDER FOR TRANSFERRING TEST TUBE**

(2013.01); *B01L 2300/12* (2013.01); *B01L 2300/123* (2013.01); *G01N 2035/00801* (2013.01)

(71) Applicant: **HITACHI HIGH-TECHNOLOGIES CORPORATION**, Tokyo (JP)

(58) **Field of Classification Search**

CPC *B01L 9/06*; *B01L 2300/0609*; *G01N 2035/00801*

(72) Inventors: **Hiroshi Ohga**, Tokyo (JP); **Tatsuya Fukugaki**, Tokyo (JP); **Tetsuya Isobe**, Tokyo (JP); **Kuniaki Onizawa**, Tokyo (JP)

See application file for complete search history.

(73) Assignee: **Hitachi High-Technologies Corporation**, Tokyo (JP)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,383,422 A 5/1983 Gordon et al.

5,897,090 A 4/1999 Smith et al.

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/959,575**

EP 2765426 A1 8/2014
JP 46-719 Y1 1/1971

(22) Filed: **Dec. 4, 2015**

(Continued)

(65) **Prior Publication Data**

US 2016/0144367 A1 May 26, 2016

Primary Examiner — Paul Hyun

(74) *Attorney, Agent, or Firm* — Mattingly & Malur, PC

Related U.S. Application Data

(63) Continuation of application No. 14/355,083, filed as application No. PCT/JP2012/082442 on Dec. 14, 2012, now Pat. No. 9,211,543.

Foreign Application Priority Data

Dec. 28, 2011 (JP) 2011-287249

(57)

ABSTRACT

A test tube holder holds various types of test tubes substantially perpendicular, and is structured to be durable against extraction and insertion of the test tubes. The test tube holder includes a housing part having a hollow portion, a holding part positioned on an upper side of the housing part and having an opening portion, which accepts a test tube, and a housing portion, which houses the accepted test tube. An elastic part is formed inside the holding part so as to abut on the housed test tube. The test tube holder has a weight housed inside the hollow portion. The holding part and the elastic part may be integrally formed. Inside the hollow portion of the housing part, besides the weight, an individual identification tag, an electromagnetic wave absorbent, and a support member for a tapered test tube can be housed in accordance with usage.

(51) **Int. Cl.**

B01L 9/06 (2006.01)

G01N 35/04 (2006.01)

G01N 35/00 (2006.01)

(52) **U.S. Cl.**

CPC **B01L 9/06** (2013.01); **G01N 35/04** (2013.01); **B01L 2200/025** (2013.01); **B01L 2300/022** (2013.01); **B01L 2300/0609**

14 Claims, 7 Drawing Sheets

